


Product Profile

A1. Model No.:		A2. Product Name:	
PN: A-RPS-S201		1080P 24GHz Radar Detection System	
B1. Product Keywords:			
<p>1) 24GHz microwave Radar Technology</p> <p>2) Support single sensor operation with wide angle (1T1R)</p> <p>3) Support one or two sensors application</p> <p>4) Screen optional, image alarm overlapping</p> <p>6) Supporting Wi-Fi hotspot connection with the smart phone/Pad, users can configure the detection distance and alarm mode. hotspot only, no internet</p> <p>7) Detection distance and alarm mode can be also set in the computer by connecting the control box to a computer with a USB to UART conversion cable</p>			
B3. Key Specifications:			
Frequency:	24.000...24.200GHz		
Dimensions:	Sensor: 106.6(W) ×72.6(H) ×32.4(D) mm. Control Box: 152.6(W) ×89.2(H) ×53.8(D) mm.		
Mounting:	Two (4.5mm) diameter mounting holes (sensor) Four (6mm) diameter mounting holes (control box)		
Transmitter Type:	FMCW		
Weight:	154.6Grams (sensor) 240Grams (control box)		
Detecting Range:	0.1 - 20m, equally divided in 5 detection zones		
Detection Zone Visualization:	Green (furthest), Yellow(middle), Red (closest)		
Detection Tolerance:	+/-30cm		
Antenna Beam Angle:	100° (Horizontal), 40° (Vertical) (1T1R)		
Video input:	1 channel AHD/CVBS		
Video output:	1 channel AHD/CVBS		
Trigger Input ×1 :	Yes, 1 channel input		
Alarm Output ×1:	Yes, 1 channel output		
IP Protection:	IP69K (sensor), IP66(Control Box)		
Vibration Rating:	5.9G		
Power Supply:	10 to 32V DC		
Video format:	CVBS(PAL, NTSC); AHD(720P, 1080P)		
Wi-Fi module:	2.4GHz (Optional)		
Operating Temperature:	-20 to +70°C		
Storage Temperature:	-30 to +80°C		
C1. Accessories:			
1 - Sensor	1 - Control Box	1 - Buzzer	1 -Cable 3m
1- Cable 3m	1- Extension Cable 1.5m	1-USB to UART Cable	1- Operation Manual & some installation accessories
D1. Packing:			
Weight Of Unit Product:		Weight Of Export Carton:	
Dimension Of Giftbox:	34.2*19.4*10cm	Dimension Of Export Carton:	42.2*35.9*41.7cm
20"/40"/40"HQ Qty:		Qty Per Carton:	
E1. Payment Term:		F1. Warranty Terms:	
T/T or L/C at sight		18 months of warranty	
G1. Certificates:		H1. Reference Price:	
		Sample:	Lead time: 14 days
I1. Remarks:			
The detection range of the default setting is 10M, which can be adjusted by our software.			